

Water Supplies for Water Injector Systems™

Mobile, convenient battery watering

Philadelphia Scientific offers several water supplies that are compatible with our Water Injector System[™] and our Water Injector System[™].

Hydro Cart™ Max

Features

- Sturdy 20-gal. (75.7-I) polypropylene tank
- Plugs into any 110 VAC outlet
- Handles like a hand truck
- · On/off switch and power indicator located on front of unit
- 30 ft. (9.14 m) of total reach 15-ft. (4.6-m) power cord plus 15 ft. (4.6 m) of 5/8-in. (1.5-cm), high-output industrial hose
- Flow indicator on the included Instant Valve Pro tells you when the Injectors have shut off and it is time to disconnect



SPECIFICATIONS

Part No. INJ-HCT

 Capacity
 20 gal. (75.7 I)

 Range
 30 ft. (9.1 m)

 Height
 40.6 in. (103.1 cm)

 Width
 19.7 in. (50.0 cm)

 Empty weight
 59 lb. (26.8 kg)

Output hose 15 ft. (4.6 m) of 5/8-in. (1.5-cm)

hose 110 VAC (8.5 Amps)

Power

Power cord

length 15 ft. (4.6 m) Wheel size 8-in. (20.3-cm)

ball bearing

Hydro Cart™ Mini

Features

- Sturdy 10-gal. (37.8-I) polypropylene tank
- Plugs into any 110 VAC outlet
- Designed for small to mid-range operations
- Handles like a hand truck
- Easy to transport; ideally suited to be taken on and off service vans
- 23 ft. (7.1 m) of total reach 13-ft. (3.9-m) power cord and 10-ft. (3.0-m) kink-resistant hose
- Flow indicator on the included Instant Valve Pro tells you when the Injectors have shut off and it is time to disconnect



SPECIFICATIONS

Part No. INJ-MINI

 Capacity
 10 gal. (37.8 l)

 Range
 23 ft. (7.1 m)

 Height
 35 in. (88.9 cm)

 Width
 15 in. (38.1 cm)

 Empty weight
 31 lb. (14.1 kg)

 Output hose
 10 ft. (3.0 m)

 Power
 110 VAC (8.5 Amps)

Power cord

length 13 ft. (3.9 m) Wheel size 8-in. (20.3-cm)

ball bearing

Bladder Tank

Features

- Unlimited mobility range
- · No AC power required to operate unit
- Sturdy 10-gal. (37.8-I) heavy duty steel tank
- · Handles like a hand truck
- Fill by attaching the input hose of your building's water supply with the Quick-Connect provided
- Internal air bladder provides pressure necessary for water flow
- · Capacity gauge indicates how full the tank is
- Tank capacity based on your pressure:

Input Pressure (PSI)	Tank Capacity (US Gal.
80 (5.5 Bar)	10 (37.8 I)
70 (4.8 Bar)	9.5 (35.9 1)
60 (4.1 Bar)	8 (30.3 I)
50 (3.4 Bar)	6 (22.7 I)



SPECIFICATIONS

Part No. INJ-T10M

 Capacity
 10 gal. (37.8 l)

 Range
 Unlimited

 Height
 41 in. (104.1 cm)

 Width
 17 in. (43.2 cm)

 Empty weight
 59.9 lb. (27.2 kg)

 Input hose
 9 ft. (2.7 m)

 Output hose
 18 ft. (5.5 m) of

5/8-in. (1.5-cm) hose

- "

Power cord length n/a

Wheel size 8-in. (20.3-cm)

ball bearing

Very low water pressure may require a booster pump.



Water Supplies for Water Injector Systems™

Changer Mounted Water Supply

Features

- Entire unit secured to the back frame of a battery changer conveniently waters batteries as they are being changed
- Sturdy 20-gal. (75.7-I) polypropylene tank cradled in a powder-coated industrial steel frame
- Control unit mounted on top of the tank includes on/ off switch, power indication, run-dry protection
- · Fits most battery changers
- Automatic pump shut off after 10 seconds of non-use
- 18 ft. (5.5 m) of 5/8-in. (1.5-cm), high-output industrial hose
- Flow indicator on the included Instant Valve Pro tells you when the Injectors have shut off and it is time to disconnect



SPECIFICATIONS Part No. INJ-PMWT-W0T Capacity 20 gal. (75.7 I) Height 41 in. (104.1 cm) Width 29 in. (73.7 cm) Depth 27 in. (68.6 cm) Weight 68 lb. (30.8 kg) Output hose 18 ft. (5.5 m) of 5/8-in. (1.5-cm) Power 110 VAC (8.5 Amps)

Power cord

length 25 ft. (7.6 m)

DirectFilf™ Hose Assembly

Features

- 18-ft. (5.5 m) rugged industrial hose
- Inline sediment filter
- Pressure regulator
- Instant Valve Pro[™] shutoff mechanism with built in flow indicator
- Use a Flow Checker to be sure output pressure from building's plumbing is adequate for use with the Water Injector System™



SPECIFICATION

Part No. INJ-DF

Range 18 ft. (5.5 m)
Empty weight 6.5 lb. (2.9 kg)
Output hose 20 ft. (6.1 m)
Isolation valve at source

recommended

The Hydro Carts™, Bladder Tank and Changer Mounted Water Supply are also compatible with the Stealth Watering System™ and our Watering Guns. Additional adaptors may be required.



Storage Battery Systems LLC N56 W16665 Ridgewood Drive Menomonee Falls, WI 53051