



MSDS (Material Safety Data Sheet)

Section I - Product Identification and company/undertaking

Product Name	: Nickel Metal Hydride Battery
Trade Name	MYD
Chemical System	: Nickel Metal Hydride
Model:	: Ni-MH A 2700mAh 3.6V
Designated for Recharge	: Yes
Effective Date	: 2023-01-02-----2023.12.31

Section II - Hazardous Ingredients

IMPORTANT NOTE: The product is a manufactured article as described in 29 CFR 1910.1200. The battery cell is contained in a hermetically-sealed case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, hazardous materials are fully contained inside the battery cell. The battery cell should not be opened or exposed to heat because exposure to the following ingredients contained within could be harmful under some circumstances. The following information is provided for the user's information only.

Chemical Name	CAS No.	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)
Nickel (powder)	7440-02-0	1 TWA	1 TWA
Nickel hydroxide	12054-48-7	1 TWA	1 TWA
Cobalt	7440-48-4	0.1 TWA	Dust & Fume 0.005
Manganese	7439-96-5	Fume: 5 Ceiling Limit	Dust: 5 Fume: 1
Lanthanum	7439-91-0	NA	NA
Cerium	7440-45-1	NA	NA
Neodymium	7440-00-8	NA	NA
Potassium hydroxide	1310-58-3	NA	2 Ceiling Limit
Sodium hydroxide	1310-73-2	2 TWA	2 Ceiling Limit
Lithium hydroxide	1310-65-2	NA	NA

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation.

- Notes: 1. Concentrations vary depending on the state of charge or discharge.
2. TWA is the time weighted average concentration over an 8-hour period.

Heavy metals in battery (2006/66/EC)

Test Items	Unit	Test Method	Result	MDL	Limit
Cadmium (Cd)	%(w/w)	Acid digestion Method, ICP-OES	N.D.	0.001	0.002



MSDS (Material Safety Data Sheet)

Lead (Pb)	%(w/w)	Acid digestion Method, ICP-OES	N.D.	0.001	-
Mercury (Hg)	%(w/w)	Acid digestion Method, ICP-OES	N.D.	0.0001	0.0005

Note:

- 0.001%=10 ppm
- N.D.=Not Detected (<MDL)
- MDL = Method Detection Limit

Remark 1:

According to the Article 21(3) of the Directive 2006/66/EC, Battery, accumulator and button cell shall include the chemical symbol Mercury when containing more than 0.0005% of Hg, the chemical symbol Cadmium when containing than 0.002% of Cd and the chemical symbol Pb when containing more than 0.004% of Pb.

Section III — Physical Data for Battery

Melting point (°F)	Boiling point (°F)	% Volatile by Volume
NA	NA	NA
Vapor Pressure (mm Hg)	Evaporation Rate Vapor	Density (Air = 1)
NA		NA
Specific Gravity (H ₂ O)	Solubility in Water	Appearance and Odor
NA	NA	No Odor

Section IV - Fire and Explosion Hazard Data

Flash Point: NA Lower Explosive Limit: NA Upper Explosive Limit: NA

Extinguishing Media: Any class of extinguishing medium may be used on the batteries or their packing material.

Special Fire Fighting Procedures: Exposure to temperatures of above 212°F can cause venting of the liquid electrolyte.

Internal shorting could also cause venting of the electrolyte. There is potential for exposure to iron, nickel, cobalt, rare earth metals (cerium, lanthanum neodymium, and praseodymium), manganese, and aluminum fumes during fire; use self-contained breathing apparatus.

Section V – First Aid Measures



MSDS (Material Safety Data Sheet)

If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately.
If electrolyte comes into contact with eyes, wash with copious amounts of water fifteen(15)minutes, and contact a physician.

Section VI - Health Hazard Data

Threshold Limit Values: See Section II

Effects of a Single (Acute) Overexposure:

Inhalation: During normal use inhalation is an unlikely route of exposure due to containment of hazardous materials within the battery case. However, should the batteries be exposed to extreme heat or pressures causing a breach in the battery cell case, exposure to the constituents may occur. Inhalation of cobalt dusts may result in pulmonary conditions.

Ingestion: If the battery case is breached in the digestive tract, the electrolyte may cause localized burns.

Skin Absorption: No evidence of adverse effects from available data.

Skin Contact: Exposure to the electrolyte contained inside the battery may result in chemical burns.

Exposure to nickel may cause dermatitis in some sensitive individuals.

Eye Contact: Exposure to the electrolyte contained inside the battery may result in severe irritation and chemical burns.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation.

Carcinogenicity:

Nickel has been identified by the National Toxicology Program (NTP) as reasonably anticipated to be a carcinogen. Cobalt has been identified by IARC as a 2B carcinogen.

Other Effects of Repeated (Chronic) Exposure:

Chronic overexposure to nickel may result in cancer; dermal contact may result in dermatitis in sensitive individuals.

Medical Conditions Aggravated by Overexposure: A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

Emergency and First Aid Procedures:

Swallowing: Do not induce vomiting. Seek medical attention immediately.

Skin: If the internal cell materials of an opened battery cell come into contact with the skin, immediately flush with water for at least 15 minutes.



MSDS (Material Safety Data Sheet)

Inhalation: If potential for exposure to fumes or dusts occurs, remove immediately to fresh air and seek medical attention.

Eyes: If the contents from an opened battery come into contact with the eyes, immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention.

Section VII - Reactivity Data

The batteries are stable under normal operating conditions.

Hazardous polymerization will not occur.

Hazardous decomposition products: oxides of nickel, cobalt, manganese, lanthanum, and cerium.

Conditions to avoid: heat, open flames, sparks, and moisture.

Potential incompatibilities (i.e., materials to avoid contact with): The battery cells are encased in a non-reactive container; however, if the container is breached, avoid contact of internal battery components with acids, aldehydes, and carbamate compounds.

Section VIII - Spill and Leak Procedures

Spill and leaks are unlikely because cells are contained in an hermetically-sealed case. If the battery case is breached, don protective clothing that is impervious to caustic materials and absorb or pack spill residues in inert material. Dispose in accordance with applicable state and federal regulations.

Section XIX - Safe Handling and Use (Personal Protective Equipment)

Ventilation Requirements: Not required under normal use.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation.

Respiratory Protection: Not required under normal use.

Eye Protection: Not required under normal use.

Gloves: Not required under normal use.

Section X- Precautions for Safe Handling and Use



MSDS (Material Safety Data Sheet)

Storage: Store in a cool place, but prevent condensation on cell or battery terminals. Elevated temperatures may result in reduced battery life. Optimum storage temperatures are between -31F and +95F.

Mechanical Containment: If there are special encapsulations or sealing requirements, consult your **MYD NEW ENERGY TECHNOLOGY LIMITED** representative about possible cell hazard precautions or limitations. Handling: Accidental short circuit will bring high temperature elevation to the battery as well as shorten the battery life. Be sure to avoid prolonged short circuit since the heat can burn attendant skin and even rupture of the battery cell case.

Batteries packaged in bulk containers should not be shaken. Metal covered tables or belts used for assembly of batteries into devices can be the source of short circuits; apply insulating material to assembly work surface. If soldering or welding to the case of the battery is required, consult your **MYD NEW ENERGY TECHNOLOGY LIMITED** representative for proper precautions to prevent seal damage or external short circuit.

Charging: This battery is designed for recharging. A loss of voltage and capacity of batteries due to self-discharge during prolonged storage is unavoidable. Charge battery before use. Observe the specified charge rate since higher rates can cause a rise in internal gas pressure which may result in damaging heat generation or cell rupture and/or venting.

Labeling: If normal label warnings are not visible, it is important to provide a device label stating:

CAUTION: Do not dispose in fire, mix with other battery types, charge above specified rate, connect improperly, or short circuit, which may result in overheating, explosion or leakage of cell contents.

Section XI – Measures for fire extinction

In case of fire, it is permissible to use any of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture. Fire fighters should wear self-contained breathing apparatus.

Section XII – Ecological information

N.A

Section XIII - Recycling and Disposal

Our Nickel Metal Hydride batteries are not defined by the federal government as hazardous waste and are safe for disposal in the normal municipal waste stream. ,

DO NOT INCINERATE or subject battery cells to temperatures in excess of +212 F. Such treatment can cause cell rupture.



MSDS (Material Safety Data Sheet)

Section XIV – Transportation

This report applies to by sea, by air and by land;

The Nickel Metal Hydride Battery according to SP A199 of the IATA Dangerous Goods regulations 64th Edition may be transported. and applicable U.S. DOT regulations for the safe transport of Ni-MH battery .

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

The Nickel Metal Hydride Battery having the potential of a dangerous evolution of heat must be prepared for transport so as to prevent: (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or, in the case of equipment, by disconnection of the battery and protection of exposed terminals); and (b) unintentional activation.

The words “Not Restricted” and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued.

The package must be handled with care and that a flammability hazard exists if the package is damaged;

Section XV – Regulatory Information

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

Section XVI – Other Information

MYD NEW ENERGY TECHNOLOGY LIMITED does not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information.

MYD NEW ENERGY TECHNOLOGY LIMITED does not offer warranty against patent infringement. Additional information is available by calling the telephone number above designated purpose.

-End-