

# Loaner Shop Chargers

## Versatility Meets Power

Choose Your Model: With Wheel  
Kit (LS) or Standalone (CCS).



Experience maximum output current from a standard 120 volt/15-amp receptacle with our Loaner Shop Charger. This powerful charger comes in two convenient models, one with a wheel and handle kit (LS) and the other as a standalone unit (CCS).



Model: LS2/24-28C1 Shown

Charge 2 - 24 Cells

28 Amp DC Rate

Ideal for Rental  
Fleets/Loaner Applications

120VAC, 15A 1PH

Shown with Dual Connector  
Option 038-199

Model	Max Cells	DC Output	ACA 120	Case
LS2/24-28C1	2-24	28	15	500
CCS2/24-28C1	2-24	28	15	500

F.O.B. First Destination, Continental USA  
Prices and Specifications subject to change  
All Prices in US Dollars

- ✓ **Powerful Performance.**
- ✓ **Durable and Compact.**

### KEY SPECIFICATIONS

- ✓ **Input:** 120 VAC, 15 amps maximum AC draw
- ✓ **Max Output:** 28 amps DC for 2 - 24 lead-acid cells, output current tapers to maintain input watts
- ✓ **Weight:** 110 lbs (Including wheel kit), 88 lbs (Without)
- ✓ **Dimensions:** LS = 36"H, 27"W, 17-3/4"D;  
CCS = 20.5"H, 17.25"W, 14.75"D
- ✓ **Control:** Automatic Start/Stop (settable for hours of recharge) with optional mechanical timer and ammeter for precise charging
- ✓ **Power Cord:** 8-foot of 14/3 SJTOW cord with molded 15-amp plug
- ✓ **DC Cables:** 8-foot, 4 AWG color-coded (red Positive, black Negative)
- ✓ **Connector:** SB175 gray connector



Empowering Industries  
for 50 Years



Phone: 314-739-1414  
Fax: 314-739-1277  
E-mail: Sales@chargingti.com  
**chargingti.com**

Charging Technologies Inc™  
4328 Bridgeton Industrial Drive  
Bridgeton, Missouri 63044

LSC-SPEC-02022024

